

# FIRESAFE™

## BUSHFIRE RATED ROLLER SHUTTER

BUSHFIRE RATED



Call for a quote  
**02 4296 9911**

TESTED BY CSIRO

BUSHFIRE RATED TO BAL A40

MEETS AUS BUSHFIRE STANDARDS

# WARRIGAL

BLINDS & SECURITY

PROTECT YOUR HOME! PROTECT YOUR FAMILY!



# FIRESAFE™ ROLLER SHUTTERS

As more Australians move to country and semi-rural areas for a better lifestyle, and our urban sprawl takes homeowners closer to bushfire prone areas, protection from bushfires has become increasingly important in Australia.

It is for this reason that CW Products, (Australia's leading supplier of roller shutters and home automation products) has developed the **FireSafe™ Bushfire Rated Roller Shutter**.

**FireSafe™** is bushfire rated to Bushfire Attack Level (BAL) A40 and is compliant with Australian Bushfire Construction Standard AS3959-2018 (Clauses 3.7 & 8.5.1).

At CW Products we're committed to helping protect Australian families and their homes!



## FIRESAFE™ BENEFITS

- Bushfire rated to Bushfire Attack Level (BAL) A40.
- Tested by CSIRO (Report# FSZ1379).
- Complies with Australian Bushfire Construction Standard AS3959-2018 (Clauses 3.7 & 8.5.1).
- Radiant heat shielding properties to 40 kW/m<sup>2</sup>.
- Commercial grade double wall extruded shutter profile for heavy duty strength and extreme heat protection.
- Heavy duty 68mm guide system for extra strength.
- Heavy duty steel axle and internal sealed bearings.
- Roll-tight design.
- Suitable for widespan widths up to 5800mm.
- High quality powder coated finish.
- Choice of profile colours.
- Either manual or motorised operation.
- FireSafe™ Authentication Plate fitted.
- Made in Australia.

## CONTROL OPTIONS



Steel Cable Winder (Up To 50Kg)\*



Spring Loaded With Key Lock



Crank Handle With Gear Ace (Up To 30Kg)



PowerSmart™ Control System With 12V Motor (Up To 50Kg)\*†



Wall Switch With 240V Electric Manual Override Motor\*



Remote Control With 240V Electric SIMU Hz Manual Override Motor



Crank Handle With 240V Electric Manual Override Motor

† When used in conjunction with an assist spring as per CW Products specifications.

\* Control options must be installed in an indoor environment.

## PROFILE COLOUR OPTIONS

Select from our wide range of high quality 36mm Extruded roller shutter profile colours.

	Cream		Black
	Magnolia Cream		Monument
	Clear Beige		Anodised Silver*
	White		Woodland Grey
	Shale Grey		

\* Not available for pelmets & side frames. Powder coated options available.

## TECHNICAL SPECIFICATIONS

<b>Bushfire Attack Level Rating</b>	BAL A40
<b>Maximum Shutter Width</b>	5800mm
<b>Maximum Shutter Height</b>	3000mm
<b>Profile Slat Covering</b>	36mm
<b>Profile Slat Thickness</b>	9.7mm
<b>Axle Types</b>	Octagonal Steel
<b>Bottom Bar Dimensions</b>	55mm x 8.5mm
<b>Guide Dimensions</b>	68mm x 25mm/14mm (Heavy Duty Guide)
<b>Paint Finish</b>	High Quality Powder Coat

**Wollongong - Nowra Distributor**

**02 4296 9911**

**Wollongong Display Centre**

**WARRIGAL** BLINDS & SECURITY

10b Commerce Drive Warilla  
warrigalblinds.com.au